



Please note that image shows a single door enclosure whereas the NSYSM1410402DP is a double door enclosure.

Available from the UK's premier enclosure distributor, iLECSYS Ltd,  
01844 397300  
sales@ilecsys.co.uk

iLECSYS have in-house capabilities to accurately machine enclosures up to 2000mm high

### Main

|                             |   |
|-----------------------------|---|
| Range                       | Spacial   |
| Product name                | Spacial SM  |
| Product or component type   | Compact enclosure   |
| Application                 | Multi-purpose   |
| Installation accessory type | Floor-standing  |
| Device composition          | 1 body<br>2 door<br>1 cable gland plate<br>1 locking system with handle: door<br>1 blocking system: left door<br>4 mounting plate bracket<br>1 mounting plate |
| Removable parts             | Door by screws hinge<br>Mounting plate by screws mounting plate bracket<br>Mounting plate bracket by screws   |
| Enclosure nominal height    | 1400 mm   |
| Enclosure nominal width     | 1000 mm   |
| Enclosure nominal depth     | 400 mm  |

### Complementary

|                            |  |
|----------------------------|--|
| Number of doors            | Front: 2 door(s)   |
| Door opening side          | Left (120 °)<br>Right (120 °)  |
| Door type                  | Plain  |
| Lock type                  | 4 points lock, handle with 5 mm double bar insert  |
| Body type                  | Single piece body with welded rear panel<br>Front part forming a rigid frame with welded corners |
| Mounting plate description | Plain  |
| Type of gland plate        | Standard   |

|                             |  |
|-----------------------------|--|
| Cable entry                 | 1 entry  |
| Material                    | Mounting plate: galvanised steel<br>Body: sheet steel<br>Door: sheet steel<br>Hinge: zamak |
| Surface finish              | Epoxy-polyester powder   |
| Colour                      | Enclosure: grey (RAL 7035)<br>Handle: black (RAL 9005)                                     |
| Accessibility for operation | Front  |

## Environment

|                         |                              |
|-------------------------|------------------------------|
| Standards               | IEC 62208                    |
| Product certifications  | DNV<br>BV<br>UL              |
| IP degree of protection | IP55 conforming to IEC 60529 |
| IK degree of protection | IK10 conforming to IEC 62262 |

## Offer Sustainability

|                            |  |
|----------------------------|--|
| Sustainable offer status   | Green Premium product  |
| REACH Regulation           | <a href="#">REACH Declaration</a>  |
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)<br><a href="#">EU RoHS Declaration</a>                              |
| Mercury free               | Yes  |
| RoHS exemption information | <a href="#">Yes</a>  |
| China RoHS Regulation      | <a href="#">Download RoHS China Declaration</a><br>Product out of China RoHS scope. Substance declaration for your information |
| Environmental Disclosure   | <a href="#">Product Environmental Profile</a>  |
| Circularity Profile        | No need of specific recycling operations   |

## Contractual warranty

|          |           |
|----------|-----------|
| Warranty | 18 months |
|----------|-----------|