## Product data sheet Characteristics

## NSYSF2012402DP

# Spacial SF enclosure with mounting plate - assembled - 2000x1200x400 mm





#### Main Range Spacial Extended range Spacial SF Application Multi-purpose Product or component Suitable enclosure type 2000 mm Enclosure nominal height Enclosure nominal width 1200 mm Enclosure nominal 400 mm depth **Enclosure mounting** Floor-standing Device composition 1 blocking system for left door 1 mounting plate 1 rear panel 1 roof 1 structure 2 sliding rails 4 mounting plate bracket 2 door 1 locking system with handle

#### Complementary

Structure type	Perforated structure with a pitch of 25 mm  Vertical uprights joined with top and bottom frames  Formed from a single section  Panels and doors built into the structure	
Door type	Plain on front	
Number of doors	2 on front face	
Door opening side	Left 120 ° Right 120 °	
Lock type	4 points lock, handle with 5 mm double bar insert on front right door	
Mounting plate description	Plain	
Type of gland plate	Without gland plate	
Accessibility for operation	Rear Front Sides of enclosure	
Removable parts	Rear panel fixed by screws Roof fixed by screws Door fixed by screws for hinge Mounting plate bracket fixed by screws Sliding rail fixed by screws Mounting plate fixed by screws for mounting plate bracket	
Material	Galvanised steel for frame Galvanised steel for uprights Polyamide 6 with 30 % fibre glass for handle Sheet steel for door Sheet steel for panels Zamak for hinge	
Surface finish	Epoxy-polyester powder	
Colour	Enclosure : grey RAL 7035 Handle : black RAL 9005	

#### Environment

Standards	IEC 62208
IP degree of protection	IP55 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262

## Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 0940 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
Product environmental profile	Available Product Environmental Profile	
Product end of life instructions	Need no specific recycling operations	

### Contractual warranty

Warranty period 18 months	