



Main

| | |
|---------------------------|---|
| Range | Spacial |
| Extended range | Spacial SF |
| Application | Multi-purpose |
| Product or component type | Suitable enclosure |
| Enclosure nominal height | 2000 mm |
| Enclosure nominal width | 1600 mm |
| Enclosure nominal depth | 400 mm |
| Enclosure mounting | Floor-standing |
| Device composition | 1 blocking system for left door 1 mounting plate 1 rear panel 1 roof 1 structure 2 sliding rails 4 mounting plate bracket 2 door 1 locking system with handle |

Complementary

| | |
|-----------------------------|---|
| Structure type | Formed from a single section Vertical uprights joined with top and bottom frames Panels and doors built into the structure Perforated structure with a pitch of 25 mm |
| Door type | Plain on front |
| Number of doors | 2 on front face |
| Door opening side | Left 120 ° Right 120 ° |
| Lock type | 4 points lock, handle with 5 mm double bar insert on front right door |
| Mounting plate description | Plain |
| Type of gland plate | Without gland plate |
| Accessibility for operation | Front Rear Sides of enclosure |
| Removable parts | Rear panel fixed by screws Roof fixed by screws Door fixed by screws for hinge Mounting plate bracket fixed by screws Sliding rail fixed by screws Mounting plate fixed by screws for mounting plate bracket |
| Material | Galvanised steel for frame Galvanised steel for uprights Polyamide 6 with 30 % fibre glass for handle Sheet steel for door Sheet steel for panels Zamak for hinge |
| Surface finish | Epoxy-polyester powder |
| Colour | Enclosure : grey RAL 7035 Handle : black RAL 9005 |

Environment

| | |
|-------------------------|------------------------------|
| Standards | IEC 62208 |
| IP degree of protection | IP55 conforming to IEC 60529 |
| IK degree of protection | IK10 conforming to IEC 62262 |

Offer Sustainability

| | |
|----------------------------------|--|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0940 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |
| Product environmental profile | Available Product Environmental Profile |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|