



Main

| | |
|----------------------|--|
| Range | Spacial |
| Product name | Spacial SMX |
| Enclosure type | Multi-purpose |
| Category | Compact enclosure |
| Nominal height | 2000 mm |
| Nominal width | 1600 mm |
| Nominal depth | 600 mm |
| Product installation | Floor-standing |
| Device composition | 1 body 1 cable gland plate 4 mounting plate bracket 2 door 1 locking system with handle (door) |

Complementary

| | |
|-----------------------------|--|
| Body type | Single piece body folded and welded |
| Door type | Plain |
| Number of doors | Front face : 2 door(s) |
| Door opening side | 120 °, reversible |
| Lock type | 3 points lock, handle with 5 mm double-bar insert |
| Mounting plate description | Without mounting plate |
| Type of gland plate | Plain |
| Accessibility for operation | Front |
| Removable parts | Door fixing: by hinges Mounting plate bracket fixing: by screws Cable gland plate fixing: by clips |
| Material | Hinge : stainless steel Body and door : stainless steel 304L Handle : zamak |
| Surface finish | Enclosure : Scotch-Brite® brushed Handle : painted |
| Thickness | 1.5 mm |
| Product weight | 200 kg |

Environment

| | |
|------------------------------|-------------------------------|
| Standards | IEC 62208 |
| Product certifications | CAN/CSA 22 UL 508 |
| IP degree of protection | IP55 conforming to IEC 60529 |
| IK degree of protection | IK10 conforming to IEC 62262 |
| Environmental characteristic | Specific hygiene Corrosive |

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Offer Sustainability

| | |
|----------------------------------|--|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0940 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold |
| Product environmental profile | Available Product Environmental Profile |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|