Product datasheet Characteristics

NSYPLM32PG

wall-mounting encl. ABS/PC monobloc IP66 H310xW215xD160mm+metal mount.plate





Main

Range	Thalassa	
Product name	Thalassa PLM	
Device short name	PLM	
Enclosure type	Multi-purpose	;
Category	Compact enclosure	
Nominal height	310 mm	
Nominal width	215 mm	
Nominal depth	160 mm	
Enclosure mounting	Wall mounted	
Device composition	1 body	
	1 door	
	1 lock	
	1 mounting plate	:
Body type	One piece moulded with notches in the rear	
	Built-in canopy	
Door type	Plain	
Lock type	3 mm double-bar lock	

Complementary

Number of locks	1	o o
Mounting plate description	Plain steel	
Accessibility for operation	Front	ri d
Removable parts	Door by hinges Mounting plate by fixing element	S
Material	ABS + PC	red iz
Colour	Grey (RAL 7035)	
Standards	NEMA classification 4X IEC 62208	- Por

NEMA classification 13

Product certifications	UL		

Environment

IP degree of protection	IP66 conforming to IEC 60529
IK degree of protection	IK10 conforming to IEC 62262
Fire resistance	960 °C conforming to IEC 62208
Ambient air temperature for operation	-4080 °C

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	1.905 kg	
Package 1 Height	22 cm	
Package 1 width	18 cm	
Package 1 Length	32 cm	

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	REACh Declaration	
REACh free of SVHC	Yes	
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	Yes	
China RoHS Regulation	China RoHS declaration Product out of China RoHS scope. Substance declaration for your information	
Environmental Disclosure	Product Environmental Profile	

Contractual warranty

Warranty 18 months	
--------------------	--