



### Main

Range	Thalassa
Accessory / separate part category	Enclosure accessory
Product or component type	Door
Application	Multi-purpose
Mounting location	Front
Range compatibility	Thalassa PLM
Device composition	1 door
Quantity per set	Set of 1

### Complementary

Material	Door: polyester reinforced with fibreglass
Colour	Door: grey (RAL 7035)
Door type	Glazed
Door opening side	Right (180 °) Left
Maximum load	50 kg/m <sup>2</sup>
Height	530 mm
Width	430 mm

### Offer Sustainability

REACH Regulation	<a href="#">REACH Declaration</a>
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.