

## AD22-LT SERIES 22.5mm LAMP TEST LED INDICATORS

- IP65 22.5mm panel mount
- High visibility in all colours
- Long Life Multi-Chip LED
- Low Power Consumption
- Cool Running
- Vibration Resistant
- CE approved
- Additional Lamp Test Input Terminal



### Specification


Ingress protection	IP65	Uninterrupted Duty	30000 Hours
Ambient temperature	-5 to +40°C	Maximum humidity	90%
Max Voltage Tolerance	+/- 20%	Vibration resistance	10-2000Hz
Insulation Type	III	Material	Flame Retardant ABS
Pollution Degree	3		

The AD22-LT Series has an additional Lamp Test Input Terminal and internal Diode blocking which allows Testing of the LED independently to other components. Terminals S, Supply and C, Common for normal energisation.

Colour	Order Codes			
	12VAC/DC	24VAC/DC	110VAC	230VAC
RED	AD22-LT-12R	AD22-LT-24R	AD22-LT-110R	AD22-LT-230R
AMBER	AD22-LT-12Y	AD22-LT-24Y	AD22-LT-110Y	AD22-LT-230Y
BLUE	AD22-LT-12B	AD22-LT-24B	AD22-LT-110B	AD22-LT-230B
GREEN	AD22-LT-12G	AD22-LT-24G	AD22-LT-110G	AD22-LT-230G
WHITE	AD22-LT-12W	AD22-LT-24W	AD22-LT-110W	AD22-LT-230W

\* Other voltages available upon request

### Dimensional Drawings



PL22-LT Series LED Indicator

Dimension	mm
A	30
B	13
C	60
D	20
E	1 - 6
F	22.5