



Sample photo

**Order symbol:** EKPE 130 G  
**Product nbr:** 2538043  
**Description:** Enclosure, PC  
**Remarks:** Grey cover

**EAN:** 6418074013583  
**EI. number:**  
 Finland 3425421  
 Italy 7501045D  
 Sweden 2538043

**Including:** Flanged Base with screws for mounting plate/DIN-rail, cover with PUR gasket and polyamide cover screws.

| Dimensions: | L   | W   | H   |
|-------------|-----|-----|-----|
| mm:         | 380 | 280 | 130 |
| inch:       | 15  | 11  | 5.1 |

| Materials:                    |              |
|-------------------------------|--------------|
| <b>Material:</b>              | PC           |
| <b>Base colour:</b>           | RAL 7035     |
| <b>Cover colour:</b>          | RAL 7035     |
| <b>Cover screws material:</b> | Polyamide    |
| <b>Cover screws colour:</b>   | Grey         |
| <b>Gasket material:</b>       | Polyurethane |

| Temperatures:      |                |
|--------------------|----------------|
| <b>Short term:</b> | -40 ... 120 °C |
| <b>Continuous:</b> | -40 ... 80 °C  |
| <b>Short term:</b> | -40 ... 250 °F |
| <b>Continuous:</b> | -40 ... 175 °F |

| Accessories: |                      |
|--------------|----------------------|
| EKPVT        | Mounting plate       |
| EKV 22       | DIN-35 Mounting rail |
| EKV 32       | DIN-35 Mounting rail |
| EKPZR        | Extension frame      |

| Rating:  |
|--|
| <b>Ingress Protection (EN 60529):</b> IP 66/67     |
| <b>Impact Resistance (EN 50102):</b> IK 08         |
| <b>Electrical insulation:</b> Totally insulated    |
| <b>Halogen free (DIN/VDE 0472, Part 815):</b> Yes  |
| <b>UV resistance:</b> UL 508                       |
| <b>Flammability Rating (UL 746 C 5):</b> UL 94 5V  |
| <b>Glow Wire Test (IEC 695-2-1) °C:</b> 960        |
| <b>NEMA Class:</b> NEMA 1, 3, 3S, 4, 4X, 6, 6P, 12 |

| Certificates:                    |
|----------------------------------|
| Germanischer Lloyd (GL)          |
| Underwriters Laboratories        |
| Det Norske Veritas               |
| Bureau Veritas                   |
| Fimko                            |
| Lloyds Register of Shipping (LR) |
| Europe EN 50298 1998             |
| UL Canada                        |
| Gost R                           |

