

Insulating wall-mounting enclosures

Specific accessories

Locking system



Characteristics

Locks and inserts for enclosures NSYPLM32G to NSYPLM86G

- The ABS/PC 310 x 215 mm enclosure is supplied with a lock with a double-bar insert as standard.
- The 308 x 255 mm enclosure is supplied with two locks with a double-bar insert as standard.
- The polyester enclosures from 430 to 847 mm high are delivered as standard with:
 - 2 locks with double-bar insert, ref. **NSYCDBPLM**,
 - or a 3-point closure with handle and lock with key 1242 E (enclosures **NSYPLM●●VG**).
- Double-bar insert ref. **NSYTDBCRN**, is placed in a rectangular escutcheon.
- A plastic key, ref. **NSYDBP**, enabling the opening of the double-bar insert, is included in the standard supply. This key can be fixed to the double-bar system to remain on the enclosure and be used as a handle.


Options

PBE01337-44
 NSYTC6CRN
 NSYTC7CRN
 NSYTC8CRN
 NSYTT6CRN
 NSYTT8CRN
 NSYTL405PLM
 NSYTL220PLM



NSYTHL1242EPLM
 NSYTHL405PLM
 NSYTHL421PLM
 NSYTHL455PLM
 NSYTHL610PLM
 NSYTHL2331APLM
 NSYTHL2433APLM
 NSYTHL3113APLM
 NSYTHL3131APLM
 NSYTHPLM

PBE01338-30



Options to transform the locks with double-bar inserts NSYPLM32G to NSYPLM86G

Changing the shape inserts for locks with keys according to the following table.

Replacement for locking handle with cylindrical barrel, delivered with all the parts required to change the lock.

Name	References	Type of barrel	References
6 mm male square	NSYTC6CRN	Key 1242 E	NSYTHL1242EPLM
7 mm male square	NSYTC7CRN	Key 405	NSYTHL405PLM
8 mm male square	NSYTC8CRN	Key 421	NSYTHL421PLM
6.5 mm male triangle	NSYTT6CRN	Key 455	NSYTHL455PLM
-	-	Key 610	NSYTHL610PLM
8 mm male triangle	NSYTT8CRN	Key 2331 A	NSYTHL2331APLM
Lock and key 405	NSYTL405PLM	Key 2433 A	NSYTHL2433APLM
Lock and key 220	NSYTL220PLM	Key 3113 A	NSYTHL3113APLM
Lock TJIS	NSYTJIS	Key 3131A	NSYTHL3131APLM
-	-	Manual	NSYTHPLM

Options to transform versions NSYPLM●●V, with retractable handle and 3-point closure

Transformation of the standard insert (barrel for key 1242E, ref. **NSYTL1242EME**) for other shape inserts or barrels according to the following table.

Name	References
5 mm double bar	NSYTDB5ME
6 mm male square	NSYTC6ME
7 mm male square	NSYTC7ME
8 mm male square	NSYTC8ME
6.5 mm male triangle	NSYTT6ME
8 mm male triangle	NSYTT8ME
Barrel and key 405	NSYTCL405ME
Reinforced key and barrel	NSYTLRME
JIS key and barrel	NSYTLJISME
Manual	NSYTMME

Insulating wall-mounting enclosures


Specific accessories

Locking system

Locks and inserts for enclosures NSYPLM108/T

- Enclosures delivered as standard with 5 mm double-bar insert.
- Double-bar insert ref. **NSYTDB5PL**, placed in a long rectangular escutcheon, activates a 4-point closure system.

PB501339-30




Options to transform the insert

The standard insert can be replaced with other shape inserts, according to the following table.

Name	References
Double-bar insert	NSYTDB5PL
6 mm male square	NSYTC6PL
7 mm male square	NSYTC7PL
8 mm male square	NSYTC8PL
6.5 mm male triangle	NSYTT6PL
7 mm male triangle	NSYTT7PL
8 mm male triangle	NSYTT8PL

PB501340-20



Options to transform for a retractable handle


The escutcheon and rosette assembly can be replaced with a lock with retractable handle equipped with inserts or barrels, according to the following table.

Name	References
5 mm double bar	NSYTEDB5PL
6 mm male square	NSYTEC6PL
7 mm male square	NSYTEC7PL
8 mm male square	NSYTEC8PL
6.5 mm male triangle	NSYTET6PL
7 mm male triangle	NSYTET7PL
8 mm male triangle	NSYTET8PL
Lock key 1242 E	NSYTEL1242EPL
Barrel and key 405	NSYTEL405PL
Reinforced key and barrel	NSYTERPL
JIS key and barrel	NSYTELJISPL
FAC key and barrel	NSYTELFACPL
Manual	NSYTEMPL

PB502869-23



DB300817-23



DB300818-11



Padlocking accessories

Padlocking system positioned around the rectangular escutcheon of the enclosures with a height of ≤ 847 mm to block access to the lock; for a $\varnothing 9$ mm padlock.

Padlocking system positioned around the long rectangular escutcheon of the enclosures ref. **NSYPLM108G/TG**, to block access to the lock; for $\varnothing 9$ mm padlock.

Padlocking system to block access to the retractable handle, for the versions **NSYPLM●●V** or optionally for enclosures ref. **NSYPLM108G/TG**, for a $\varnothing 9$ mm padlock.

References

NSYKPLM	NSYBCPL	NSYBCME
----------------	----------------	----------------