

# Steel wall-mounting enclosures

## Accessories

### Hoisting



Characteristics	Eyebolts
	Set of two M8 eyebolts. They are fixed directly to the body of the floor-standing enclosure. Cannot be installed with the canopy in place or if it is planned to put one.
Material	Zinc-coated moulded steel
Maximum load	200 kg per enclosure when slinging at 60°
Supply	Reinforcing brackets attached to the rings (these brackets also act as a drilling template)
<b>Reference</b>	
Batch of 2 M8 eyebolts	<b>NSYAELYTCR8</b>

### Protection



Characteristics	Protection canopy				
	Direct fixing to the body of the enclosure by 4 M6 screws. To be used for all outdoor installations.				
Material	Galvanised steel				
Finish	Epoxy-polyester paint				
Colour	RAL 7035 grey				
Supply	Delivered with the fixings required for installation				
Depth (mm)	Width (mm)	F (mm)	G (mm)	H (mm)	References
150	200	36	75	23	<b>NSYTJ2015</b>
	250	36	75	23	<b>NSYTJ2515</b>
	300	36	75	23	<b>NSYTJ3015</b>
	400	36	75	23	<b>NSYTJ4015</b>
	500	36	75	23	<b>NSYTJ5015</b>
200	500	36	130	23	<b>NSYTJ5020</b>
	600	36	130	23	<b>NSYTJ6020</b>
	250	36	130	23	<b>NSYTJ2520</b>
	300	36	130	23	<b>NSYTJ3020</b>
	400	36	130	23	<b>NSYTJ4020</b>
	800	36	130	23	<b>NSYTJ8020</b>
250	400	42	150	48	<b>NSYTJ4025</b>
	500	42	150	48	<b>NSYTJ5025</b>
	600	42	150	48	<b>NSYTJ6025</b>
	800	42	150	48	<b>NSYTJ8025</b>
300	600	42	200	48	<b>NSYTJ6030</b>
	800	42	200	48	<b>NSYTJ8030</b>
	1000	42	200	48	<b>NSYTJ10030</b>
	1200	42	200	48	<b>NSYTJ12030</b>
400	600	42	300	48	<b>NSYTJ6040</b>
	800	42	300	48	<b>NSYTJ8040</b>
	1000	42	300	48	<b>NSYTJ10040</b>
	1200	42	300	48	<b>NSYTJ12040</b>

