



Sample photo

Order symbol: PC 100/75 HG
Product nbr: 6011302
Description: Enclosure, PC
Remarks: Grey cover

EAN: 6418074024404
EI. number:
 Finland 3422251
 Denmark 8212022292
 Italy 7351027
 Sweden 2535513

Including: Base with TPE gasket and screws for mounting plate/DIN-rail, cover with polyamide cover screws and wing heads for cover screws.

Dimensions:				Rating:			
	L	W	H				
mm:	130	80	75	Ingress Protection (EN 60529): IP 66/67			
inch:	5.1	3.1	3	Impact Resistance (EN 50102): IK 08			
Materials:				Electrical insulation: Totally insulated			
Material:	PC			Halogen free (DIN/VDE 0472, Part 815): Yes			
Base colour:	RAL 7035			UV resistance: UL 508			
Cover colour:	RAL 7035			Flammability Rating (UL 746 C 5): UL 94 5V			
Cover screws material:	Polyamide			Glow Wire Test (IEC 695-2-1) °C: 960			
Cover screws colour:	Grey			NEMA Class: NEMA 1, 4, 4X, 6			
Gasket material:	TPE			Certificates:			
Temperatures:				Germanischer Lloyd (GL)			
Short term:	-40 ... 120 °C			Underwriters Laboratories			
Continuous:	-40 ... 80 °C			Det Norske Veritas			
Short term:	-40 ... 250 °F			Fimko			
Continuous:	-40 ... 175 °F			Europe EN 50298 1998			
Accessories:				UL Canada			
MIV 100	Mounting plate			Gost R			
MIN 5	DIN-15 Mounting rail						
MIN 10	DIN-15 Mounting rail						
MIV 5	DIN-35 Mounting rail						
MIV 10	DIN-35 Mounting rail						
FP A 100/130	Front plate						
HFP 130	Front plate hinge series						

