



Sample photo

Order symbol: PC 125/125 HG
Product nbr: 6011310
Description: Enclosure, PC
Remarks: Grey cover

EAN: 6418074022127
EI. number:
 Finland 3420335
 Denmark 8212022111
 Italy 7351065
 Sweden 2535536

Including: Base with TPE gasket and screws for mounting plate/DIN-rail, cover with polyamide cover screws and wing heads for cover screws.

| Dimensions: | L | W | H |
|-------------|-----|-----|-----|
| mm: | 130 | 130 | 125 |
| inch: | 5.1 | 5.1 | 4.9 |

| Materials: | |
|-------------------------------|-----------|
| Material: | PC |
| Base colour: | RAL 7035 |
| Cover colour: | RAL 7035 |
| Cover screws material: | Polyamide |
| Cover screws colour: | Grey |
| Gasket material: | TPE |

| Temperatures: | |
|--------------------|----------------|
| Short term: | -40 ... 120 °C |
| Continuous: | -40 ... 80 °C |
| Short term: | -40 ... 250 °F |
| Continuous: | -40 ... 175 °F |

| Accessories: | |
|--------------|--------------------------|
| MIV 125 | Mounting plate |
| MIN 10 | DIN-15 Mounting rail |
| MIV 10 | DIN-35 Mounting rail |
| FP A 125/130 | Front plate |
| HFP 130 | Front plate hinge series |

| Rating: |
|---|
| Ingress Protection (EN 60529): IP 66/67 |
| Impact Resistance (EN 50102): IK 08 |
| Electrical insulation: Totally insulated |
| Halogen free (DIN/VDE 0472, Part 815): Yes |
| UV resistance: UL 508 |
| Flammability Rating (UL 746 C 5): UL 94 5V |
| Glow Wire Test (IEC 695-2-1) °C: 960 |
| NEMA Class: NEMA 1, 4, 4X, 6 |

| Certificates: |
|---------------------------|
| Germanischer Lloyd (GL) |
| Underwriters Laboratories |
| Det Norske Veritas |
| Fimko |
| Europe EN 50298 1998 |
| UL Canada |
| Gost R |

