



Sample photo

**Order symbol:** PC 125/35 LG  
**Product nbr:** 6012307  
**Description:** Enclosure, PC  
**Remarks:** Grey cover

**EAN:** 6418074022073  
**EI. number:**  
 Finland 3420323  
 Denmark 8212022069  
 Italy 7351040  
 Sweden 2535521

**Including:** Base with TPE gasket and screws for mounting plate/DIN-rail, cover with polyamide cover screws and wing heads for cover screws.

Dimensions:				Rating:
L	W	H		
mm:	130	130	<b>Ingress Protection (EN 60529):</b> IP 66/67	
inch:	5.1	5.1	<b>Impact Resistance (EN 50102):</b> IK 08	
Materials:				Electrical insulation: Totally insulated
<b>Material:</b>	PC			<b>Halogen free (DIN/VDE 0472, Part 815):</b> Yes
<b>Base colour:</b>	RAL 7035			<b>UV resistance:</b> UL 508
<b>Cover colour:</b>	RAL 7035			<b>Flammability Rating (UL 746 C 5):</b> UL 94 5V
<b>Cover screws material:</b>	Polyamide			<b>Glow Wire Test (IEC 695-2-1) °C:</b> 960
<b>Cover screws colour:</b>	Grey			<b>NEMA Class:</b> NEMA 1, 4, 4X, 6
<b>Gasket material:</b>	TPE			Certificates:
Temperatures:				<b>Germanischer Lloyd (GL)</b>
<b>Short term:</b>	-40 ... 120 °C			<b>Underwriters Laboratories</b>
<b>Continuous:</b>	-40 ... 80 °C			<b>Det Norske Veritas</b>
<b>Short term:</b>	-40 ... 250 °F			<b>Fimko</b>
<b>Continuous:</b>	-40 ... 175 °F			<b>Europe EN 50298 1998</b>
Accessories:				<b>UL Canada</b>
MIV 125	Mounting plate			<b>Gost R</b>
MIN 10	DIN-15 Mounting rail			
MIV 10	DIN-35 Mounting rail			
FP A 125/130	Front plate			
HFP 130	Front plate hinge series			

