



Sample photo

**Order symbol:** PC 200/75 HT  
**Product nbr:** 6011926  
**Description:** Enclosure, PC  
**Remarks:** Smoked transparent cover

**EAN:** 6418074021984  
**EI. number:**  
 Finland 3421612  
 Denmark 8212022551  
 Italy 7352123

**Including:** Base with TPE gasket and screws for mounting plate/DIN-rail, cover with polyamide cover screws and wing heads for cover screws.

Dimensions:				Rating:
	L	W	H	
mm:	255	180	75	<b>Ingress Protection (EN 60529):</b> IP 66/67
inch:	10	7.1	3	<b>Impact Resistance (EN 50102):</b> IK 08
Materials:				<b>Electrical insulation:</b> Totally insulated
<b>Material:</b>	PC			<b>Halogen free (DIN/VDE 0472, Part 815):</b> Yes
<b>Base colour:</b>	RAL 7035			<b>UV resistance:</b> UL 508
<b>Cover colour:</b>	Smoked grey			<b>Flammability Rating (UL 746 C 5):</b> UL 94 5V
<b>Cover screws material:</b>	Polyamide			<b>Glow Wire Test (IEC 695-2-1) °C:</b> 960
<b>Cover screws colour:</b>	Black			<b>NEMA Class:</b> NEMA 1, 4, 4X, 6, 12, 13
<b>Gasket material:</b>	TPE			Certificates:
Temperatures:				<b>Germanischer Lloyd (GL)</b>
<b>Short term:</b>	-40 ... 120 °C			<b>Underwriters Laboratories</b>
<b>Continuous:</b>	-40 ... 80 °C			<b>Det Norske Veritas</b>
<b>Short term:</b>	-40 ... 250 °F			<b>Fimko</b>
<b>Continuous:</b>	-40 ... 175 °F			<b>Europe EN 50298 1998</b>
Accessories:				<b>UL Canada</b>
MIV 200	Mounting plate			<b>Gost R</b>
MIN 15	DIN-15 Mounting rail			
MIN 20	DIN-15 Mounting rail			
MIV 15	DIN-35 Mounting rail			
MIV 20	DIN-35 Mounting rail			
FP A 200/180	Front plate			
HFP 180	Front plate hinge series			

