



Sample photo

Order symbol: PC 2819 18 G
Product nbr: 5330370
Description: Enclosure, PC
Remarks: Grey cover

EAN: 6418074005465
El. number:
 Finland 3423707
 Italy 7401025D
 Sweden 2539412

Including: Base with screws for mounting plate/DIN-rail, cover with PUR gasket and polyamide cover screws.

Dimensions:		L	W	H	Rating:
mm:		278	188	180	Ingress Protection (EN 60529): IP 66/67
inch:		10.9	7.4	7.1	Impact Resistance (EN 50102): IK 08/09
Materials:					
Material:		PC			
Base colour:		RAL 7035			
Cover colour:		RAL 7035			
Cover screws material:		Polyamide			
Cover screws colour:		Grey			
Gasket material:		Polyurethane			
Temperatures:					
Short term:		-40 ... 120 °C			
Continuous:		-40 ... 80 °C			
Short term:		-40 ... 250 °F			
Continuous:		-40 ... 175 °F			
Accessories:					
EKJVT		Mounting plate			
EKV 12		DIN-35 Mounting rail			
EKV 22		DIN-35 Mounting rail			
EKJZR		Extension frame			
		Electrical insulation: Totally insulated Halogen free (DIN/VDE 0472, Part 815): Yes UV resistance: UL 508 Flammability Rating (UL 746 C 5): UL 94 5V Glow Wire Test (IEC 695-2-1) °C: 960 NEMA Class: NEMA 1, 3, 3S, 4, 4X, 6, 6P, 12			
Certificates:					
		Underwriters Laboratories Canadian Standards Association Fimko Europe EN 50298 1998			

