



Sample photo

Order symbol: PC 2828 18 G
Product nbr: 5330372
Description: Enclosure, PC
Remarks: Grey cover

EAN: 6418074005540
El. number:
 Finland 3423715
 Italy 7401045D
 Sweden 2539420

Including: Base with screws for mounting plate/DIN-rail, cover with PUR gasket and polyamide cover screws.

Dimensions:				Rating:	
	L	W	H		
mm:	278	278	180	Ingress Protection (EN 60529): IP 66/67	
inch:	10.9	10.9	7.1	Impact Resistance (EN 50102): IK 08/09	
Materials:				Electrical insulation: Totally insulated	
Material:	PC			Halogen free (DIN/VDE 0472, Part 815): Yes	
Base colour:	RAL 7035			UV resistance: UL 508	
Cover colour:	RAL 7035			Flammability Rating (UL 746 C 5): UL 94 5V	
Cover screws material:	Polyamide			Glow Wire Test (IEC 695-2-1) °C: 960	
Cover screws colour:	Grey			NEMA Class: NEMA 1, 3, 3S, 4, 4X, 6, 6P, 12	
Gasket material:	Polyurethane			Certificates:	
Temperatures:				Underwriters Laboratories	
Short term:	-40 ... 120 °C			Canadian Standards Association	
Continuous:	-40 ... 80 °C			Fimko	
Short term:	-40 ... 250 °F			Europe EN 50298 1998	
Continuous:	-40 ... 175 °F				
Accessories:					
EKOVT	Mounting plate				
EKV 22	DIN-35 Mounting rail				
EKOZR	Extension frame				

