



Sample photo

Order symbol: PCM 175/75 T
Product nbr: 6016920
Description: Enclosure, PC
Remarks: Smoked transparent cover

EAN: 6418074024510
El. number:
 Finland 3422262
 Denmark 8212027433
 Sweden 2535437

Including: Base with metric knock-outs and TPE gasket and screws for mounting plate/DIN-rail, cover with polyamide cover screws and wing heads for cover screws.

Dimensions:			L		W		H	
mm:	180	180	75					
inch:	7.1	7.1	3					
Materials:								
Material:	PC							
Base colour:	RAL 7035							
Cover colour:	Smoked grey							
Cover screws material:	Polyamide							
Cover screws colour:	Black							
Gasket material:	TPE							
Temperatures:								
Short term:	-40 ... 120 °C							
Continuous:	-40 ... 80 °C							
Short term:	-40 ... 250 °F							
Continuous:	-40 ... 175 °F							
Accessories:								
MIV 175	Mounting plate							
MIN 15	DIN-15 Mounting rail							
MIV 15	DIN-35 Mounting rail							
FP A 175/180	Front plate							
HFP 180	Front plate hinge series							
Rating:								
Ingress Protection (EN 60529): IP 66/67								
Impact Resistance (EN 50102): IK 08								
Electrical insulation: Totally insulated								
Halogen free (DIN/VDE 0472, Part 815): Yes								
UV resistance: UL 508								
Flammability Rating (UL 746 C 5): UL 94 5V								
Glow Wire Test (IEC 695-2-1) °C: 960								
NEMA Class: NEMA 1, 4, 4X, 6, 12, 13								
Certificates:								
Germanischer Lloyd (GL)								
Underwriters Laboratories								
Det Norske Veritas								
Fimko								
Europe EN 50298 1998								
UL Canada								
Gost R								

