



Sample photo

Order symbol: PCM 200/100 XG
Product nbr: 6015326
Description: Enclosure, PC
Remarks: Grey cover

EAN: 6418074038357
EI. number:
 Finland 3421622
 Denmark 8212027349
 Sweden 2535357

Including: Base with metric knock-outs and PUR gasket and screws for mounting plate/DIN-rail, cover with polyamide cover screws and wing heads for cover screws.

| Dimensions: | | L | W | H | Rating: |
|-------------------------------|--|---------------------------|-----|-----|---|
| mm: | | 255 | 180 | 100 | Ingress Protection (EN 60529): IP 66/67 |
| inch: | | 10 | 7.1 | 3.9 | Impact Resistance (EN 50102): IK 08 |
| Materials: | | | | | |
| Material: | | PC | | | |
| Base colour: | | RAL 7035 | | | |
| Cover colour: | | RAL 7035 | | | |
| Cover screws material: | | Polyamide | | | |
| Cover screws colour: | | Grey | | | |
| Gasket material: | | Polyurethane | | | |
| Temperatures: | | | | | |
| Short term: | | -40 ... 120 °C | | | |
| Continuous: | | -40 ... 80 °C | | | |
| Short term: | | -40 ... 250 °F | | | |
| Continuous: | | -40 ... 175 °F | | | |
| Accessories: | | | | | |
| MIV 200 | | Mounting plate | | | |
| MIN 15 | | DIN-15 Mounting rail | | | |
| MIN 20 | | DIN-15 Mounting rail | | | |
| MIV 15 | | DIN-35 Mounting rail | | | |
| MIV 20 | | DIN-35 Mounting rail | | | |
| FP A 200/180 | | Front plate | | | |
| HFP 180 | | Front plate hinge series | | | |
| | | | | | Electrical insulation: Totally insulated |
| | | | | | Halogen free (DIN/VDE 0472, Part 815): Yes |
| | | | | | UV resistance: UL 508 |
| | | | | | Flammability Rating (UL 746 C 5): UL 94 5V |
| | | | | | Glow Wire Test (IEC 695-2-1) °C: 960 |
| | | | | | NEMA Class: NEMA 1, 4, 4X, 6, 12, 13 |
| Certificates: | | | | | |
| | | Germanischer Lloyd (GL) | | | |
| | | Underwriters Laboratories | | | |
| | | Det Norske Veritas | | | |
| | | Fimko | | | |
| | | Europe EN 50298 1998 | | | |
| | | UL Canada | | | |
| | | Gost R | | | |

